

Overview of Cabot-Koppers Superfund Site

Presented to University of Florida Environmental Law Class Professor Mary Jane Angelo

March 29, 2007

Presented by

John J. Mousa, Ph.D. Alachua County Environmental Protection Department


EPA Superfund Process



- Preliminary Assessment / Site Inspection (PA/SI)
 - Investigate site conditions
- Hazard Ranking System (HRS) Scoring
 - Determine if risks significant to place site on the National Priorities List (NPL)
- NPL Site Listing Process

 List of most serious sites identified for possible long-term cleanup
- Remedial Investigation/ Feasibility Study (RI/FS)
 - Determines nature and extent of contamination, risks to human health, remediation alternatives
- Record of Decision (ROD)
 - Explains and documents cleanup alternatives selected by USEPA
- Remedial Design / Remedial Action (RD/RA)
 - Prepare and implement plans for selected site remedies
- Construction CompletionIdentifies completion of cleanup activities
- **Post Construction Completion**
 - Ensures remedies selected provide long-term protection of human health and the environment.

Source EPA







Cabot-Koppers Superfund Site Koppers Chemicals of Concern

- Creosote DNAPL Dense Non-Aqueous Phase Liquid
 - Napthalene
 - Benzene
 - Carcinogenic aromatic chemicals (PAHs)
 - Phenols
- > Pentachlorophenol
 - Chlorinated phenols
 - Dioxin
- > CCA
 - Arsenic

DNAPL tends to move down vertically in environment

Cabot-Koppers Superfund Site Former Koppers North Lagoon Area







Cabot-Koppers Superfund Site Site History

Cabot Site --49 acres

- History of pine tar & charcoal production
- Pine tar/pine oil production by Cabot since 1945
- Product isolation in 3 unlined lagoons (1949)
- Cabot sold site (1967)
- Developer breechs product lagoons 1970's
- Pine tars and oils discharged to wetlands and creek



Cabot-Koppers Superfund Site Site History

Alachua Coun Florida

Cabot Site

- Remaining lagoon sludges mixed with site soils (1970)
- Shopping center built on site
- Stormwater ponds built on top of former lagoons
- Malodorous leachate appears in Main Street ditch



Cabot-Koppers Superfund Site Cabot Chemicals of Concern



- ▶ Pine tars / oils
 - Phenols
 - Terpenes (pine compounds) (odorous)
 - Napthalenes
- ➤ Tars, Diesel and Creosote Northeast Lagoon
 - Napthalenes
 - Phenols
 - Hydrocarbons





Cabot-Koppers Superfund Site Key Participants in Process



Regulators

- US EPA Region 4 <u>Primary Decision Maker</u> and Site Manager (EPA)
- Florida Dept. of Environmental Protection (FDEP)
- Alachua County Environmental Protection Dept. (ACEPD)

Principal Responsible Parties (PRPs)

- Beazer East, Inc. Koppers Site (Beazer)
- Cabot Corporation Cabot Site (Cabot)

Stakeholders and Interested Parties

- City of Gainesville/Gainesville Regional Utilities (GRU)
- · Local Community and Elected Officials
- Koppers Industries
- Alachua County Health Department
- · Surrounding Neighborhood

Status of Cabot and Koppers Sites in Superfund Process



- Preliminary Assessment / Site Inspection (PA/SI)
- · Hazard Ranking System (HRS) Scoring
- NPL Site Listing Process

<<Both Sites here in 1983!!

 Remedial Investigation/ Feasibility Study (RI/FS)

<< Koppers Site is here (2007)

- Record of Decision (ROD)
- Remedial Design / Remedial Action (RD/RA)
- Construction Completion
- Post Construction Completion

<< Cabot Site is here (2007)

Cabot-Koppers Superfund Site Regulatory Actions



- 1983 Sites (Cabot/ Koppers) placed on NPL Superfund list
- 1985-1987- FDEP installs leachate collection system on Cabot site; conducts initial remedial investigation (RI)
- 1988 Beazer and Cabot sign Consent Order with USEPA to complete RI, develop Feasibility Study (FS) for remedial alternatives
- 1990-- EPA Record of Decision (ROD) for combined sites Remedies selected <u>Link:http://cfpub.epa.gov./superrods/schrods.cfm</u>
- 1991-1995-- Cabot signs Consent Order with EPA, implements ROD remedial actions at the Cabot site
- 1991 Beazer agrees to implement ROD at Koppers site in response to EPA unilateral administrative order
- 1994 Beazer implements shallow groundwater recovery remedy for Koppers site

Remedial Actions Implemented Cabot Site





- Soil contamination below direct contact health risk levels
- Contaminated soils in NE Lagoon partially removed
- Shallow groundwater containment system installed along N. Main St.
- Discharge of contaminated water to city sewer
- · Concrete lining of N. Main St. ditch
- Groundwater containment system continues to operate
- Site in Post Construction Phase monitoring



Fig. Source: Cabot Briefing to EPA Jan 27, 2005










Cabot- Koppers Superfund Site Regulatory Actions (cont'd)




- 1999 -- Amended FS for Koppers Site produced by EPA due to additional contamination found
- 2001 -- Amended ROD for Koppers soil remedy proposed by EPA
- 2001-- EPA presents proposed Amended ROD to local community
- 2001 -- Local community rejects EPA proposed solutions asks for further investigation of underlying Hawthorn group formations
- 2002 EPA requests additional investigation of deeper soil and groundwater zones by Beazer


Cabot-Koppers Superfund Site Koppers Site 2001 Amended ROD Original Assumptions and Remedial Plans


- Surficial groundwater contamination
 - Continue boundary groundwater extraction system
- Surface soil direct contact threat
 - Remove surface soils and cap source areas
- Hawthorn Group clays under source areas prevent migration to lower aquifers
- Solidify and stabilize source areas, horizontal flow barriers, rely on clays to prevent downward migration.
- RECENT INVESTIGATIONS HAVE CONFIRMED THAT ORIGINAL ASSUMPTIONS WERE INCORRECT AND CONTAMINANTS HAVE MIGRATED TO DEEPER HAWTHORN AND FLORIDAN AQUIFER ZONES UNDER THE SITE





















Cabot-Koppers Superfund Site Results of Additional Investigations (2002-2004)



- Original assumptions about site geology are incorrect.
 - Hawthorn clay not a barrier to migration of creosote
 - Free product creosote and groundwater contamination in intermediate Hawthorn Formations (40-90ft bls)
 - Groundwater contamination in Floridan Aquifer (130 ft bls)
 - Napthalene (1200 ug/L) in Floridan near North Lagoon Clean-up standard (14 ug/L)
- Migration of contamination to City well field possible

Cabot-Koppers Superfund Site Additional Activities at Koppers Site (2002-2005)





- Develop Revised FS -- Beazer
- Investigate source removal options -- Beazer
- Immediate interim remedial actions requested City/County
- Sentinel wells between site and City wellfield -- GRU
- Technical experts hired to review Beazer data -- GRU
- Groundwater modeling study -- Beazer
- Pilot remedies & interim remedial actions evaluated Beazer
- Additional Floridan aquifer monitoring -- Beazer


Cabot-Koppers Superfund Site Additional Activities at Koppers Site (2005-2006)




- Beazer Groundwater model predicts no threat to wellfield. City and County disagree.
- GRU experts indicate that groundwater contamination travel time to wellfield could be as low as 4 to 5 years.
- GRU experts recommend multilevel Floridan monitoring wells on site and near source areas
- EPA orders Beazer to install and sample multilevel Floridan wells on site
- Beazer performs additional source sampling for Risk Assessment and setting clean-up goals for soils









Cabot-Koppers Superfund Site Soil Sampling for Risk Assessment



- Supplemental Soil Sampling –Fall 2006
 - Arsenic, Dioxin, Creosote components, Pentachlorophenol
- Source areas are known to be heavily contaminated.
- Outside source area zones
 - 0 6" and 6" to 2ft zones primarily
- Establish direct contact risk, leaching risk
- Evaluate airborne risks from dust
- · Establish clean-up criteria for soils
- Issues
 - Industrial vs Residential standards
 - Removal of source material
 - Engineering controls and restrictions on site.

Cabot-Koppers Superfund Site Current Activities and Issues



- Additional Floridan Wells at Boundary
 - Investigate deeper zones at 350 ft BLS for contamination
 - Test hydraulic properties of Floridan zones
- EPA needs to decide on extent of threat to wellfield
- Containment of Floridan contamination needs evaluation.
- Intermediate Hawthorn aquifer needs further investigation
- Soil testing to establish clean-up standards for soils
- Pilot study to test source removal from Hawthorn
- Upgrade of boundary well containment system
- Complete revised feasibility study / remedial alternatives
- County, City and GRU continue to urge expedited actions



Overview of Cabot-Koppers Superfund Site

Presented to
University of Florida Environmental Law Class
Professor Mary Jane Angelo

March 29, 2007

Presented by

John J. Mousa, Ph.D. Alachua County Environmental Protection Department